



Alloy Hollow Side-Eject Tine - .750MT x 4.750L x .470OD R108-9159



Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

Replaces

Toro 108-9159

Specifications

| | |
|----------------------------------|-------------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Hollow Side-Eject |
| B - Tine Mounting Dia. | .750 in (19mm) |
| C - Tine Length | 4.75 in (121mm) |
| D - Tine Tip Outside (Hole) Dia. | .470 in (11.9mm) |
| E - Tine Tip Inside (Core) Dia. | .300 in (7.6mm) |
| F - Tine Wall Thickness | .058 in (1.5mm) |
| Savings | Volume Buy |

Fits Models

Toro Fairway Aerator
Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648
Toro ProCore 660
Toro ProCore 864
Toro ProCore 880

Gritmaster

309 Percy Osborn Road Morningside, 4001
0313035785

<https://gritmaster.rrproducts.com/>



**Alloy Hollow Side-Eject Tine - .750MT x
4.750L x .470OD**
R108-9159



Toro ProCore 648s

Gritmaster

309 Percy Osborn Road Morningside, 4001
0313035785

<https://gritmaster.rrproducts.com/>