



# Hypro Centrifugal Pump - Reverse Rotation

## RHY9203C-R



### Details

Hypro centrifugal pump is designed for agricultural and industrial spraying and transfer of a variety of fluids, including water, insecticides, herbicides, wettable powders, emulsives, liquid fertilizers, etc. Made of cast iron and 316 stainless steel, it has a minimum of surfaces to wear and no valves. It is very durable, easy to maintain and well suited for pumping abrasive and corrosive materials. Features: Maximum Flow 136 GPM. Maximum Pressure 180 psi. Maximum Speed 6000 rpm. Viton/Ceramic Seals. 5/8" Solid Shaft. 1-1/2" inlet, 1-1/4" outlet.

- Centrifugal pump
- Few surfaces to wear
- No valves
- Durable
- Easy to maintain
- Designed for pumping abrasive and corrosive materials
- Maximum flow 136 GPM
- Maximum speed 6000 rpm.
- Maximum pressure 180 psi.
- Viton/Ceramic seals
- 5/8" solid shaft
- 1-1/2" inlet, 1-1/4" outlet.
- Cast Iron

### Specifications

Manufacturer

Pentair Shurflo

### Gritmaster

309 Percy Osborn Road Morningside, 4001  
0313035785

<https://gritmaster.rrproducts.com/>