



Alloy Hollow Side-Eject Tine with Carbide Tip - .750MT x 5.500L x .425OD

R201446



Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine. A carbide tip is then added for even longer life. The advantage of using carbide-tipped tines is the ability to maintain your maximum aerating depth consistently over the life of the tines.

Replaces

R&R Products R108-9176

Specifications

| | |
|----------------------------------|--|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Hollow Side-Eject with Carbide Tip |
| B - Tine Mounting Dia. | .750 in (19mm) |
| C - Tine Length | 5.500 in (140mm) |
| Carbide Tip | Carbide Tip |
| D - Tine Tip Outside (Hole) Dia. | .425 in (10.7mm) |
| E - Tine Tip Inside (Core) Dia. | .275 in (7mm) |
| F - Tine Wall Thickness | .072 in (1.8mm) |
| Savings | Volume Buy |

Gritmaster

309 Percy Osborn Road Morningside, 4001
0313035785

<https://gritmaster.rrproducts.com/>



Alloy Hollow Side-Eject Tine with Carbide Tip - .750MT x 5.500L x .425OD

R201446



Fits Models

John Deere Aercore 1000
John Deere Aercore 1500
John Deere Aercore 2000
John Deere Aercore 800
Ryan GA30
Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648
Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

Gritmaster

309 Percy Osborn Road Morningside, 4001
0313035785

<https://gritmaster.rrproducts.com/>