



# Alloy Machined Side-Eject Tine - .625MT x 4.000L x .350OD R201520



## Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

## Specifications

|                                  |                           |
|----------------------------------|---------------------------|
| Manufacturer                     | R&R Products              |
| A - Tine Type                    | Alloy Machined Side-Eject |
| B - Tine Mounting Dia.           | .625 in (15.9mm)          |
| C - Tine Length                  | 4 in (102mm)              |
| D - Tine Tip Outside (Hole) Dia. | .350 in (8.9mm)           |
| E - Tine Tip Inside (Core) Dia.  | .220 in (5.5mm)           |
| F - Tine Wall Thickness          | .065 in (1.7mm)           |

## Fits Models

Jacobsen GA-24  
Ryan GA30  
Ryan Greensaire II

## Gritmaster

309 Percy Osborn Road Morningside, 4001  
0313035785

<https://gritmaster.rrproducts.com/>