



# Alloy Hollow Tine - .750MT x 6.500L x .5700D R201656



## Details

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

## Specifications

|                                  |                  |
|----------------------------------|------------------|
| Manufacturer                     | R&R Products     |
| A - Tine Type                    | Alloy Hollow     |
| B - Tine Mounting Dia.           | .750 in (19mm)   |
| C - Tine Length                  | 6.5 in (165mm)   |
| D - Tine Tip Outside (Hole) Dia. | .515 in (13.1mm) |
| E - Tine Tip Inside (Core) Dia.  | .300 in (7.6mm)  |
| F - Tine Wall Thickness          | .072 in (1.8mm)  |

## Fits Models

Toro ProCore 1298  
Toro ProCore 440  
Toro ProCore 648  
Toro ProCore 660  
Toro ProCore 864  
Toro ProCore 880  
Toro ProCore 648s

## Gritmaster

309 Percy Osborn Road Morningside, 4001  
0313035785

<https://gritmaster.rrproducts.com/>