

Clutch - Xtreme Pto Clutch R116-1620X





Details

Xtreme Clutches feature machined pulleys, Cool Coil technology, high performance bearings, stainless steel straps and rivets, Xtreme's Tough Wire Protection System and a replaceable bearing, the Xtreme design is pure performance in every aspect.

- Machined Pulleys CNC machined billet pulleys are stronger, quieter, smoother and maintain stable and faster blade speeds.
- Fatboy Bearings Increased the size of the pulley bearing to imporve bearing life.
- High Temp Bearing Xtreme's special blend of bearing grease is rated more than two times what is required, delivering Xtreme bearing life
- Triple Protected Wires Every Xtreme clutch has an integrated watertight connection with three layers of protection.
- Replaceable Bearing Xtreme mower clutches have a repaceable pulley bearing!
- Stainless Steel Rivets Xtreme clutches use tough stainless steel brake rivets for long and safe service
- Xtreme "Cool Coil" The "Xtremely Cool Coil "
 runs over 20% cooler. Electromagnetic
 clutches run very hot. Most competitive
 clutches run around 220 degrees. The Xtreme
 proprietary composite coil runs 175 degrees.
 The difference is simple: Less heat = ex

Replaces

Exmark 109-9282, 116-1604

Toro 116-1604

Gritmaster

309 Percy Osborn Road Morningside, 4001

https://gritmaster.rrproducts.com/



Clutch - Xtreme Pto Clutch R116-1620X



Specifications

Manufacturer Xtreme Equipment

Fits Models

Exmark Lazer Z E-Series
Exmark Lazer Z S-Series
Exmark Pioneer S-Series
Exmark Quest SP Series
Exmark Vertex S-Series
Toro Z Master Commercial 4000

Gritmaster

309 Percy Osborn Road Morningside, 4001

https://gritmaster.rrproducts.com/